

Релейные стабилизаторы для котлов (250 Вт до 2 кВт.)

Модель

Диапазон входного напряжения, В

Количество

ступеней



[Volter-0.25P](#)

155-250

4

[Volter-0.5P](#)

155-250

4

[Volter-1P](#)

155-250

4

Модель

Диапазон входного напряжения, В

Количество

ступеней



[Volter-2P](#)

155-250

4

Переносные стабилизаторы



Модель

Диапазон входного напряжения, В

Количество ступеней

[СНПТО 2 \(γ\) - 2 кВт \(3 кВа\)](#)

150-260

7

[СНПТО 2 \(ш\) - 2 кВт \(3 кВа\)](#)

130-270

7

[СНПТО 2 \(пт\) - 2 кВт \(3 кВа\)](#)

150-245

16

[СНПТО 2 \(птс\) - 2 кВт \(3 кВа\)](#)

170-265

16

Высокоточный стабилизатор

Модель

Диапазон входного напряжения, В

Количество ступеней



[Высокоточный стабилизатор Volter-2000](#)

150-245

16

Стабилизаторы напряжения 4 - 14 кВт

Модель

Диапазон входного напряжения, В

Количество ступеней



10-245V
стабилизатор напряжения, В



10-270V
стабилизатор напряжения, В



10-270V
стабилизатор напряжения, В



10-270V
стабилизатор напряжения, В



1500270 Vestec
стабилизатор напряжения, В



1500280 Vestec
стабилизатор напряжения 9-14, ВТ повышенной точности



1500310 Vestec
стабилизатор напряжения 18-27, ВВТ



1500360 Vestec

1. The first step is to identify the problem. In this case, the problem is that the system is not working properly.

2. The second step is to gather information. This includes checking the logs, looking at the error messages, and talking to the users.

3. The third step is to analyze the data. This involves looking for patterns in the data and trying to figure out what is causing the problem.

4. The fourth step is to develop a solution. This could involve changing the code, updating the hardware, or changing the configuration.

5. The fifth step is to test the solution. This involves running the system and seeing if the problem is fixed.

6. The sixth step is to implement the solution. This involves putting the changes into production.

7. The seventh step is to monitor the system. This involves keeping an eye on the system to make sure it is working properly.

8. The eighth step is to document the solution. This involves writing a report about what was done and why.

9. The ninth step is to communicate the solution. This involves telling the users that the problem has been fixed.

10. The tenth step is to evaluate the solution. This involves looking at the results and seeing if the problem has been solved.

Three Vmax 1000mAh 12V NiMH batteries are shown. They are silver-colored with black and white terminals. The front battery has a blue digital display and a yellow label with a warning symbol.

PAGE 40 MIT

Three VARTA AGA batteries are shown connected in series. Each battery is a rectangular metal case with a black top cover. The front of each battery has a label with the VARTA logo and technical specifications. The batteries are connected by metal terminals on top.

21/10/19

10 / 11



Синхронизаторы, стабилизаторы, инверторы, Етап 9-11 кВт



930 = 330 Etalon 91